

Clean Johnson

Claim 1. An automobile communications method for an on-board mobile station in across a plurality of radio zones which are consecutively arranged along a road, comprising: providing each of the radio zones with a plurality of communication frequencies, switching between the plurality of communication frequencies within each of the radio zones using a time division scheme; such that a different time slot is allocated for adjacent radio zones for each of the plurality of communication frequencies, and switching a time slot allocated to the on-board mobile station to continuously communicate with the on-board mobile station across the plurality of radio zones.

Claim 2. The automobile communications method of claim 1, wherein the time slot used for communication with the onboard mobile station is switched in such a manner that communication with the on-board mobile station is continuously performed at one of the plurality of communication frequencies over the plurality of radio zones.

Claim 3. The automobile communications method to claim 1, wherein the time slot is switched in such a manner that communication with the on-board mobile station is continuously performed at different ones of the plurality of communication frequencies over the radio zones.

Claim 4. An automobile communications method between an Onboard mobile station and a fixed station system comprising a plurality of radio zones which consecutively arranged along a road, comprising: providing each of the radio zones with a plurality of communication frequencies, switching between the plurality of communication frequencies within each of the radio zones using a time division scheme, such that a different time slot is allocated for each adjacent radio zone for each of the plurality of communication frequencies, and continuously communicating with the on-board mobile station at one of the plurality of communication frequencies over the plurality of radio zones.

Claim 5. The automobile communications method of claim 4, wherein the plurality of communication frequencies in each radio zone are generated from a single reference frequency in accordance with a predetermined conversion to be in a frequency-coherence state.

Claim 6. The automobile communications system of claim 4, wherein a predetermined number N (N is an integer equal to or greater than 2) of time slots are determined in one period in each of the radio zones, wherein one time slot is assigned to a single on-board mobile station and M (M is an integer equal to or greater than 2) predetermined communication frequencies are sequentially switched from one to another at a time interval of every N/M time slot.

Claim 7. The automobile communications method of claim 6, wherein the time slot allocated to the on-board mobile station is switched in such a way that the on-board-mobile station uses the one of the plurality of communication frequencies over the plurality of radio zones.

Claim 8. The automobile communications method of claim 4, wherein each of the plurality of communication frequencies is used for both transmission and reception to perform communication with the on-board mobile station according to a TDMA/TDD (Time Division Multiple Access/Time Division Duplex) scheme.

Claim 9. The automobile communications method of claim 4, wherein the plurality of communication frequencies in each radio zone are generated from a single reference frequency in accordance with a predetermined conversion to be in a frequency-coherence state, wherein each of the of communication frequencies is used for both transmission and reception to perform communication with the on-board mobile station according to a TDMA/TDD (Time Division Multiple Access/Time Division Duplex) scheme.

Claim 10. The automobile communications method of claim 4, wherein the plurality of communication frequencies comprises a plurality of different pairs of first frequencies and second frequencies, wherein the first frequencies are generated from

one reference frequency in accordance with first predetermined conversion so that the first frequencies are in a frequency-coherence state over the radio zones.

Claim 11. The automobile communication method according to claim 10, wherein the on-board mobile station generates a transmission local signal of the second frequency from a radio signal received from the fixed station system in accordance with a second predetermined conversion.

Claim 12. The automobile: communication method according to claim 11, wherein the fixed station system generates a reception local frequency from the first frequency in accordance with the second predetermined conversion as used by the on-board mobile station so that the reception local frequency and a radio signal received from the onboard mobile station are in a frequency-coherence state.

Claim 13. An automobile communications system comprising: an on-board mobile station movable on a road, a plurality of fixed stations comprising a plurality of radio zones consecutively arranged on the road, wherein each of the plurality of fixed stations are communicable with the on-board mobile station using a plurality of communication frequencies, and a control station controlling the plurality of fixed stations performing continuous communication with the on-board mobile station by switching time slots in adjoining radio zones with the on-board mobile station to communications using one of the plurality of communication frequencies in adjoining

Art Unit: 2686

radio zones and switching a time slot allocated to the on-board mobile station in accordance with the switching in the plurality of fixed stations and by switching between the plurality a communication frequencies in each of the plurality of radio zones using a time division scheme such that adjoining fixed stations communicate using different frequencies of the plurality of communications frequency at any given time.

Claim 14. The automobile communications of claim 13, wherein the time slot allocated to the on-board mobile station is switched from one to another in such a manner that communication with the on-board mobile station is continuously performed at the one of the plurality of communication frequencies over the of radio zones.

Claim 15. The automobile communications system of claim 13 wherein each of the plurality of fixed stations comprising: a frequency generator for generating the plurality of communication frequencies from the signal of a reference frequency input from the control station, a selector for selecting one communication frequency in use from the plurality of communication frequencies under control of the control station, a time-division controller for allocating a time slot to communication with the on-board mobile station at the one of the plurality of communication frequencies, and an interface for transmission and reception of signals to and from the control station.

16. The automobile communications system of claim 15, wherein each of the plurality of communication frequencies is used for both transmission and reception to

perform communication with the on-board mobile station according to a TDMA/TDD scheme.

17. The automobile communications system of claim 15, wherein frequency generator generates the plurality of communication frequencies so that the plurality of communication frequencies are frequency-coherent to the reference frequency wherein each of the plurality of communication frequencies is used for transmission and reception, and wherein the time-division controller performs communication with the on board mobile station according to a TDMA/TDD (Time Division Multiple Access/Time Division Duplex) scheme.

Claim 18. The automobile communications system of claim 15, wherein the plurality of communication frequencies comprises a plurality of different pairs of first frequencies and second frequencies, wherein the frequency generator generates the first frequencies form one reference frequency in accordance with a first predetermined conversion so that the first frequencies are in a frequency-coherence state.

Claim 19. The automobile communication method according to claim 18, wherein each of the fixed stations generates a reception local frequency from the first frequency in accordance with a second predetermined conversion as used by the onboard mobile station so that the reception local frequency and a radio signal received from the onboard mobile station are in a frequency coherence state.

Claim 20. The automobile communications system of according to claim 13, wherein the on-board mobile station comprises: a frequency-in-use regenerator for regenerating the one of the plurality of communication frequencies from a signal received from a fixed station which forms a radio zone: for communication, and a communication controller controlling communication with the fixed station using the allocated time slot at the one of the plurality of communication frequencies.

Claim 21. The automobile communications system of claim 20, wherein each of the plurality of communication frequencies is used for transmission and reception, and the communication controller carries out communication with the fixed station according to a TDM/TDD scheme.

Claim 22. (Currently amended) The automobile communications system of according to claim 20, wherein each of the plurality of communication frequencies is used for transmission and reception frequencies, wherein the frequency-in-use regenerator comprises: a demodulator for demodulating the received signal, and a phase controller for performing phase control on a signal of an oscillation frequency based on an output of the demodulator such that the demodulator acquires synchronization; and wherein the communication controller carries out communication with the fixed station according to a TDMA/TDD scheme using the oscillation frequency as a transmission local frequency.

*See
Applicant
Fig. 3*

Claim 23. The automobile communications system of claim 20, wherein the frequency-in-use regenerator comprises: a demodulator for demodulating the received signal using an oscillation frequency, and a phase controller for performing; phase control on the signal of the oscillation frequency based on an output of the demodulator such that the demodulator acquires synchronization, and wherein the on-board mobile station further comprises: a converter for generating a transmission local frequency from the signal of the oscillation frequency in accordance with the predetermined conversion, and a modulator for generating a transmission signal using the transmission local frequency.

Claim 24. The automobile communication system according to claim 23, wherein the predetermined conversion of the converter is the same as a predetermined conversion for generating a reception local signal from a transmission frequency at each fixed station.

Claim 25. The fixed station in the automobile communications system of claim 13, comprising: a communication frequency generator that generates the plurality of communication frequencies from the signal of a reference frequency coming from the control station, a selector for selecting one communication frequency from the plurality of communication frequencies under control of the control station, a time-division controller for allocating a time slot to communication with the on-board mobile station at

Art Unit: 2686

the one of the plurality of communication frequencies, and an interface for implementing transmission and reception of signals to and from the control station.

Claim 26. The fixed station of claim 25, wherein each of the plurality of pain communication frequencies is used for transmission and reception, and communication with the can-board mobile station is carried out according to a TDMA/TDD scheme.

Claim 27. The fixed station of claim 25, wherein each of the, plurality of communication frequencies is used for transmission and reception, the communication frequency, generator generates the plurality of communication frequencies in each radio zone so that the plurality of communication frequencies are frequency-coherent to the reference frequency, and the time division controller carries out communication with the on-board mobile station according to a TDMA/TDD scheme.

Claim 28. The fixed station, of claim 25, wherein the plurality of communication frequencies comprises a plurality of different pairs of a first frequency and a second frequency, and the communication frequency generator generates the first frequency from the reference frequency in accordance with a first predetermined conversion in such a manner that those first frequencies are in a frequency coherence state over the plurality of radio zones.

Claim 29. The fixed station of according-to claim 25, wherein the plurality of communication frequencies comprises a plurality of different pairs of a first frequency and a second frequency, and a reception local frequency for demodulating a received radio signal from the on-board mobile station which is generated from the first frequency in accordance with a second predetermined conversion so that the reception local signal is frequency-coherent to the received radio signal from the on-board mobile station.

Claim 30. The, on-board radio mobile station in the automobile communications communication a system of in claim 13, comprising: a frequency-in-use regenerator for regenerating the one of the plurality communication frequencies from a signal received from a fixed station which forms a radio zone for communication, and a communication controller for communication with the fixed station using the allocated tune slot based on the one of the plurality of communication frequencies.

Claims 31. The on-board radio mobile station of claim. 30, wherein each of the plurality of communication frequencies is used for transmission and reception, and the communication controller carries out communication with the fixed station according to a TDMA/TDD scheme.

Claims 32. The on-board radio mobile station of claim 30, wherein each of the plurality of communication frequencies is used for transmission and reception; wherein

the frequency-in-use regenerator comprises: a demodulator for demodulating the received signal, and a phase controller performing phase control on a signal of an oscillation frequency based on an output of the demodulator such that the demodulator acquires synchronization, wherein the communication controller carries out communication with the fixed station according to a TDMA/TDD scheme by using the oscillation frequency as a transmission local frequency.

Claim 33. The on-board radio mobile station according to claim 30, wherein the frequency-in-use regenerator comprises: a demodulator for demodulating a. received signal of an oscillation frequency, and a phase controller performing phase control on the signal of the oscillation frequency based on an output of the demodulator such that the demodulator acquires synchronization; a-ad wherein the on-board radio mobile station further comprises: a converter for generating a transmission local frequency from the signal of the oscillation frequency in accordance with a predetermined conversion, and a modulator for generating a transmission signal using the transmission local frequency.

Claim 34. The on-board radio mobile station according to claim 30, wherein the predetermined conversion of the converter is the same as a predetermined conversion for generating a reception local signal from is transmission frequency at each fixed station.

Claim 35. The control station in the automobile communications system of claim 13, comprising: a reference frequency generator that generates the reference frequency signal for producing the plurality of communication frequencies in each fixed station, a communication controller for transmitting and receiving signals to and from the plurality of fixed stations, and a system controller controlling the one of the plurality of communication frequencies for the plurality of fixed stations at a predetermined timing in such a way as not to permit simultaneous transmission at a same communication frequency in adjoining radio zones.

Claim 36. The fixed station of claim 28, wherein the plurality of communication frequencies comprises a plurality of different pairs of a first frequency and a second frequency, and a reception local frequency for demodulating a received radio signal from the on-board mobile station is generated from the first frequency in accordance with a second predetermined conversion so that the reception local signal is frequency-coherent to the received radio signal from the on-board mobile station.

37. The method of claim 1, wherein the plurality of communication frequencies in each radio zone are generated from a single reference frequency.

38. The method of claim 4, wherein the plurality of communication frequencies in each radio zone are generated from a single reference frequency.

39. The system of claim 13, wherein the plurality of communication frequencies in each radio zone are generated from a single reference frequency.

40. An automobile communications method between an on-board mobilestation and a fixed station system in a plurality of radio zones which are consecutively arranged along a road, comprising: providing each of the radio zones with a plurality of communication frequencies, controlling a communication frequency used in each of the radio zones using a time division scheme such that simultaneous transmission at a same communication frequency is not permitted in adjoining radio zones and different time slats are allocated for communications at a same communication frequency in adjoining radio zones, and continuously communicating with the on-board mobile station at a same communication frequency over the radio zones, wherein a predetermined number N (N is an integer equal to or greater than 2) of time slots are determined in one period in each of the radio zones, wherein one time slot is assigned to a single on-board mobile station and M (M is an integer equal to or greater than 2) communication frequencies are sequentially switched from one to another at a timing of every N/M time slot.

41. The automobile communications method of claim 40, wherein the time slot allocated to the on-board mobile station is switched in such a way that the on-board Mobile station uses a same communication frequency over the plurality of radio zones.

Application/Control Number: 09/348,169
Art Unit: 2686

Page 15